



Switches Not Shown For Clarity

Notes:

- 1- Heights shown are PVP standards pump centerline heights can be raised or lowered.
- 2- Switches and dampeners are optional. Check build sheets for equipment supplied.
- 3- Flex joints not recommended
- 4- When installing pump keep area under pump clear for maintenance
- 5- Swan neck can rotate 90° left or right
- 6- Motor can be mounted on the right or left side
- 7- To remove belt guard, 40-inches is required above the pump. Covers can be split to be removed horizontally

Total Equip. Weight = 1900 lbs
WT. w/o dampeners = 1180 lbs

Notes			
Material: -----			
Rev	Description	Date	By
0	Initial Release	9/16/2020	ABB
Revision History			

THIS DRAWING AND ALL INFORMATION IS THE PROPERTY OF

PENN VALLEY PUMP CO., INC.

998 EASTON ROAD - WARRINGTON, PA 18976

PHONE: (215) 343-8750 www.pennvalleypump.com

PVP

Penn Valley Pump

ALL INFORMATION CONTAINED IN THIS DOCUMENT IS BOTH CONFIDENTIAL AND PROPRIETARY TO PVP. NO LICENSE, EXPRESSED OR IMPLIED, UNDER ANY PATENT, COPYRIGHT, OR TRADE SECRET IS GRANTED OR IMPLIED BY THE CONVEYANCE OF THIS DOCUMENT. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, TRANSMITTED, TRANSFERRED, STORED IN A RETRIEVAL SYSTEM, TRANSLATED TO ANY LANGUAGE OR COMPUTER LANGUAGE, IN ANY FORM BY ANY MEANS ELECTRONIC, MECHANICAL, OR OTHERWISE.

CUSTOMER: Penn Valley Pump

LOCATION: Internal

TITLE: 6DDSX107 Side Mount

SCALE: N/A

DATE: 9/17/2020

DR. BY: -

PLOT DATE: -

DRAWING NO. PVD769

SHEET 1 OF 1