

-20-2 12<u>1</u> BELT TENSION
ADJUSTMENT



- 1- HEIGHTS SHOWN ARE PVP STANDARDS
  PUMP CENTERLINE HEIGHTS CAN BE
  RAISED OR LOWERED.
  2- SWITCHES AND DAMPENERS ARE
  OPTIONAL. CHECK BUILD SHEETS FOR
  EQUIPMENT SUPPLIED.
  3- FLEX JOINTS NOT RECOMMENDED
  4- WHEN INSTALLING PUMP KEEP AREA
  UNDER PUMP CLEAR FOR MAINTENANCE

INITIAL RELEASE

9/16/2020

ABB

ijË

REVISION HISTORY

DESCRIPTION

Per
enn Vall
ey Pu
ag U
F 88 P

THIS DRAWING AND ALL INFORMATION IS THE PROPERTY OF

ENN VALLEY PUMP CO., INC. 8 EASTON ROAD - WARRINGTON, PA 18976 ONE: (215) 343-8750 www.pennvalleypump.com

ALL INFORMATION CONTAINED IN THIS DOCUMENT IS BOTH CONFIDENTIAL AND PROPRIETARY TO PAP, NO LICENSE, EXPRESSED OR IMPLED, UNDER AMY PATENT, COPYRIGHT, OR TRADE SECRET IS GRANTED OR IMPLIED BY THE CONNEYMORG OF THIS DOCUMENT. NO PART OF THIS DOCUMENT MAY BE REPRODUCED, TRANSLATED, TRANSLATED, TRANSLATED, TRANSLATED, TRANSLATED, TRANSLATED, TRANSLATED, TRANSLATED TO ANY LANGUAGE OR COMPUTER LANGUAGE, IN ANY FORM PLOT DATE

BY ANY MEANS ELECTRONIC, MECHANICAL, OR OTHERWISE. CUSTOMER: Penn Valley Pump

LOCATION: Internal 3DDSX11 Piggy Back DRAWING NO. SHEET 1 OF 1 PVD804